



The EASYMIG 140 is a semi-automatic machine that combines MIG/MAG, cored wire and MMA welding processes. Thanks to its user-friendly interface, the voltage and wire speed settings are made easier. Ultra-light, it is easy to carry around. The EASYMIG 140 is recommended for welding steel, stainless steel and aluminium.



Ultra-light and portable

- 7.8 kg weight.
- Ergonomic handle.

Easy set up



- Voltage set selection from 15 to 21 V.
- Wire speed selection from 3 to 9 m/min.

Sturdy build quality

- Reinforced mechanical structure.
- Pads for shock and vibration absorption.

Integrated wire feeder

- ø100 (1 kg) wire reels.
- 2 rollers motor
- Supplied rollers :
 - steel : 0.8
 - no gas : 0.9

MIG/MAG Torch

- Supplied with a removable torch 150 A - 2.20 m fitted for steel.
- EURO torch for a fast assembly/disassembly.

Simplified display



- 2 colour LED to display :
- Thermal protection.
 - Power up.

MIG/MAG - MMA

- Wire diameter Ø 0.6 mm to 0,8 mm.
- Électrode Ø 1.6 mm à 3.2 mm.

Polarity reversal cable

- For NO GAS welding.

Features



Inverter technology to ensure an excellent welding current quality and a low electric consumption.



Can weld rutile electrodes . Antisticking (prevents electrode sticking at start).



Can weld :
- MIG/MAG wire with gas
- MIG/MAG cored wire without gas

NO GAS ready to weld


This process allows :

- Welding with cored wire (requires polarity reversal).
- Allows outdoor welding (not wind. affected...)
- Increased portability due to absence of gas bottles.
- Ideal for outdoors work on thin metal sheets.

Includes

- **Earth clamp**
(cable 1.6 m / 16 mm²)
- **Electrode holder**
(cable 1.6 m / 10 mm²)
- **Accessories bag**
 - Contact tip 0.9 mm.
 - Gas nozzle « gas ».
 - Tightening key for contact tips.
 - Gas tube 1 m.
 - 2 clamps for the gas tube.



50/60hz	AM	MMA I ²	min▷max	ømm		100	Electronic Control	équipé d'origine / original equipment / originalausstattung / equipamiento de fabrica		EN60974-1 (40°C)				cm/kg
				GAS	NO GAS			IA (60%)	X% (Iz max)	IA (60%)	X% (Iz max)			
230V 1~	16A	20▷120A	30▷140A	0.6 - 0.8	0.9	✓		0.8 - 0.9	0.8	80A	140A 15%	70A	120A 15%	38x16x35 / 7,8